

15-819M Data, Code, Decisions

Assignment 3 (Σ 50) due by Thu 11/05/2009

André Platzer

Carnegie Mellon University, Computer Science Department, Pittsburgh, PA aplatzer@cs.cmu.edu

Disclaimer: No solution will be accepted that comes without an **explanation!**

Exercise 1 JML Queue Specifications (12p)

Please give a JML specification of a queue by completing the specification (not implementation) of the following class, including invariants, preconditions, and postconditions:

```
public class Queue {
    Object [] array;
    int size;
    int first;
    int next;

    public Queue(int max) {
        // ...
    }

    public int size() {
        // ...
    }

    public void enqueue(Object x) {
        // ...
    }

    public Object dequeue() {
        // ...
    }
}
```

Exercise 2 JML List Specifications (8p)

Please give a JML specification for the following class. In particular, specify the method `size()`.

```
public class List {
    Object first;
    List rest;
```

```

public List(Object first , List rest) {
    this.first = first;
    this.rest = rest;
}

public int size() {
    // ...
}
}

```

Exercise 3 JML Basics (10p)

1. JML only allows pure functions in expressions. Is there a good reason for this? Why?
2. Can you change JML so that it would allow arbitrary functions in expressions? What is the effect of this change on runtime monitoring and on formal verification?
3. Are pure methods really pure? Give an example of a pure method and a JML specification such that the pure method changes the result of one of the JML expressions, or explain why there is no such example.

Exercise 4 Formal Semantics of Java (20p)

Develop a formal semantics for a Java fragment that includes all relevant detail to give a semantics to the following code snippet

```

try {
    if (++x < x+1) {
        x = 2*x;
        throw e;
    } else {
        x = 0;
    }
}
catch (SomeException t) {
    x = x*x;
}

```

The semantics does not need to capture all of Java but only programs that include the elements that you find in the above example program.